Marici 205-190 Matt TW

Tunable white


Tunable white LED opbouw downlight. Voorzien van decoratieve aluminium (99,9%) matte reflector en gesatineerde PS Microprisma afscherming. Tunable white - dynamisch mengen van licht kleur tussen 2700K en 6500K (**CRI>93, R9>83**). Zeer geschikt als basis verlichting in gangen of kantoren. Brede bundel (>74°) en lage verblinding op maximaal vermogen (UGR<19). Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne DALI DT8 driver met mogelijkheid tot doorlussen. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (L90B10 125.000 uur). Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

*Tunable white modular surface mounted LED downlight. High gloss aluminium reflector (99,9%) with matt finish and satinated PS Microprism diffuser. Tunable white - dynamic mixing of light colour, linear colour mixing between 2700K and 6500K (**CRI>93, R9>83**). Wide beam angle (>74°) and low glare at maximum power (UGR<19). White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal DALI DT8 driver with possibility for through-wiring. Direct connection to 220-240VAC. Low maintenance and high life expectancy (L90B10 125.000 hours). High color consistency SDCM <2. Five years warranty.*

Wattage *Watts*	**Kleur** *Colour*	**Lumen*** *Lumen**	**CRI** *CRI*	**Gewicht (kg)** *Weight (kg)*	**Noodvoorz. (u)** *Emergency (h)*	**Dali-2** *Dali-2*	**Casambi** *Casambi*
12w	2700-6500k	1275-1351	>93	2,8	1/3	62006WPB.12.TWM	62006WPB.12.TWMC
18w	2700-6500k	1789-1896	>93	2,8	1/3	62006WPB.18.TWM	62006WPB.18.TWMC
26w	2700-6500k	2625-2781	>93	2,8	1/3	62006WPB.26.TWM	62006WPB.26.TWMC
34w	2700-6500k	3153-3340	>93	2,8	1/3	62006WPB.34.TWM	62006WPB.34.TWMC

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*








OPBOUW DOWNLIGHTS

SURFACE MOUNTED DOWNLIGHTS



Opties:l
- Schuinstelling voor aflopende plafonds op aanvraag
- Andere RAL kleur

Opties:
- *Diagonal attachment for sloped ceilings on request*
- *Different RAL Colour*



62006WPB.12M.TW
12w 2700-6500k 1275-1351lm
ηLB 100%

melis lighting