

Marici 205-190 DARKLIGHT SUSPENDED



PENDEL ARMATUREN SUSPENDED LUMINAIRES


Ronde LED pendel downlight. Voorzien van trompetvormige darklight reflector van 99,98% hoogglans aluminium met brede bundel (>77°) en hoge efficiency (max 142lm/w) met CRI>80. Zeer lage verblinding (UGR<19, 9-18w) en minimale helderheid door uniek darklight reflector ontwerp. Wit (RAL 9003) gelakte stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer goed toepasbaar in vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round suspended LED downlight. Trumpet shaped darklight reflector made of 99,98% specular aluminium with wide beam angle (>77°) with high efficiency (max 142lm/w) and CRI>80. Very low glare (UGR<19, 9-18w) and minimal brightness due to unique darklight reflector design. White painted steel body (RAL9003). Delivered including internal driver and connector block. Direct connection to mains. Ideal for lighting high rooms like lobby's, churches and mosques. Delivered including 3 meter cable. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
9w	3000k	1277	250	2,8	1	62020WPN.00.DK	62020WPN.01.DK	62020WPN.02.DK	62020WPN.05.DK
12w	3000k	1777	350	2,8	1	62006WPN.00.DK	62006WPN.01.DK	62006WPN.02.DK	62006WPN.05.DK
18w	3000k	2486	500	2,8	1	62017WPN.00.DK	62017WPN.01.DK	62017WPN.02.DK	62017WPN.05.DK
25w	3000k	3395	700	2,8	1	62010WPN.00.DK	62010WPN.01.DK	62010WPN.02.DK	62010WPN.05.DK
33w	3000k	4248	900	2,8	1	62015WPN.00.DK	62015WPN.01.DK	62015WPN.02.DK	62015WPN.05.DK
9w	4000k	1344	250	2,8	1	62021WPN.00.DK	62021WPN.01.DK	62021WPN.02.DK	62021WPN.05.DK
12w	4000k	1869	350	2,8	1	62007WPN.00.DK	62007WPN.01.DK	62007WPN.02.DK	62007WPN.05.DK
18w	4000k	2612	500	2,8	1	62018WPN.00.DK	62018WPN.01.DK	62018WPN.02.DK	62018WPN.05.DK
25w	4000k	3566	700	2,8	1	62012WPN.00.DK	62012WPN.01.DK	62012WPN.02.DK	62012WPN.05.DK
33w	4000k	4460	900	2,8	1	62016WPN.00.DK	62016WPN.01.DK	62016WPN.02.DK	62016WPN.05.DK

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



Opties:)


- 90CRI of 97CRI

Opties:

- 90CRI or 97CRI

Levensduurverwachting (uren)
Life expectancy (hours)

Watt	L90B10
9	79.000
12	78.000
18	70.000
25	64.000
33	57.000



62007WPN.00.DK
12w 4000k 1869lm
ηLB 84,0%

melis lighting

