

Marici 205-190 DARKLIGHT SUSPENDED




Ronde LED pendel downlight. Voorzien van trompetvormige darklight reflector van 99,98% hoogglans aluminium met brede bundel (>77°) en hoge efficiency (max 177lm/w) met **CRI>93 (R9>88)**. Zeer lage verblinding (UGR<19, 9-18w) en minimale helderheid door uniek darklight reflector ontwerp. Wit (RAL 9003) gelakte stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer goed toepasbaar in vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Round suspended LED downlight. Trumpet shaped darklight reflector made of 99,98% specular aluminium with wide beam angle (>77°) with high efficiency (max 177lm/w) and **CRI>93 (R9>88)**. Very low glare (UGR<19, 9-18w) and minimal brightness due to unique darklight reflector design. White painted steel body (RAL9003). Delivered including internal driver and connector block. Direct connection to mains. Ideal for lighting high rooms like lobby's, churches and mosques. Delivered including 3 meter cable. Low maintenance and high life expectancy. High color consistency SDCM <2. Fast and easy mounting. Five years warranty.


Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali-2 Dali-2	Casambi Casambi
5w	3000k	841	150	3,0	1	62020WPNS.00.DK	62020WPNS.01.DK	62020WPNS.02.DK	62020WPNS.05.DK
9w	3000k	1395	250	3,0	1	62020WPN.00.DK	62020WPN.01.DK	62020WPN.02.DK	62020WPN.05.DK
12w	3000k	1935	350	3,0	1	62006WPN.00.DK	62006WPN.01.DK	62006WPN.02.DK	62006WPN.05.DK
18w	3000k	2723	500	3,0	1	62017WPN.00.DK	62017WPN.01.DK	62017WPN.02.DK	62017WPN.05.DK
26w	3000k	3723	700	3,0	1	62010WPN.00.DK	62010WPN.01.DK	62010WPN.02.DK	62010WPN.05.DK
34w	3000k	4671	900	3,0	1	62015WPN.00.DK	62015WPN.01.DK	62015WPN.02.DK	62015WPN.05.DK
5w	4000k	841	150	3,0	1	62021WPNS.00.DK	62021WPNS.01.DK	62021WPNS.02.DK	62021WPNS.05.DK
9w	4000k	1395	250	3,0	1	62021WPN.00.DK	62021WPN.01.DK	62021WPN.02.DK	62021WPN.05.DK
12w	4000k	1935	350	3,0	1	62007WPN.00.DK	62007WPN.01.DK	62007WPN.02.DK	62007WPN.05.DK
18w	4000k	2723	500	3,0	1	62018WPN.00.DK	62018WPN.01.DK	62018WPN.02.DK	62018WPN.05.DK
26w	4000k	3723	700	3,0	1	62012WPN.00.DK	62012WPN.01.DK	62012WPN.02.DK	62012WPN.05.DK
34w	4000k	4671	900	3,0	1	62016WPN.00.DK	62016WPN.01.DK	62016WPN.02.DK	62016WPN.05.DK

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



PENDEL ARMATUREN SUSPENDED LUMINAIRES



62020WPNS.00.DK
5w 3000k 841lm
ηLB 100%

melis lighting