

Marici 205-190 MATT SUSPENDED

Extreem krachtige ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) matte reflector (UGR<18). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer brede bundel (>74,0°) en hoge efficiency (max 131lm/w) met **CRI>93**. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.




Powerful round suspended LED downlight. High gloss aluminium reflector (99,9%) with matt (M) finish (UGR<18). Extra wide beam angle (>74,0°) and high efficiency (max 131lm/w) with **CRI>93**. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy. High color consistency SDCM <2. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali-2 Dali-2	Casambi Casambi
5w	3000k	620	150	3,0	1	62020WPNS.00.M	62020WPNS.01.M	62020WPNS.02.M	62020WPNS.05.M
8w	3000k	1029	250	3,0	1	62020WPN.00.M	62020WPN.01.M	62020WPN.02.M	62020WPN.05.M
12w	3000k	1428	350	3,0	1	62006WPN.00.M	62006WPN.01.M	62006WPN.02.M	62006WPN.05.M
17w	3000k	2008	500	3,0	1	62017WPN.00.M	62017WPN.01.M	62017WPN.02.M	62017WPN.05.M
25w	3000k	2746	700	3,0	1	62010WPN.00.M	62010WPN.01.M	62010WPN.02.M	62010WPN.05.M
33w	3000k	3445	900	3,0	1	62015WPN.00.M	62015WPN.01.M	62015WPN.02.M	62015WPN.05.M

5w	4000k	620	150	3,0	1	62021WPN.00.M	62021WPN.01.M	62021WPN.02.M	62021WPN.05.M
8w	4000k	1029	250	3,0	1	62021WPN.00.M	62021WPN.01.M	62021WPN.02.M	62021WPN.05.M
12w	4000k	1428	350	3,0	1	62007WPN.00.M	62007WPN.01.M	62007WPN.02.M	62007WPN.05.M
17w	4000k	2008	500	3,0	1	62018WPN.00.M	62018WPN.01.M	62018WPN.02.M	62018WPN.05.M
25w	4000k	2746	700	3,0	1	62012WPN.00.M	62012WPN.01.M	62012WPN.02.M	62012WPN.05.M
33w	4000k	3445	900	3,0	1	62016WPN.00.M	62016WPN.01.M	62016WPN.02.M	62016WPN.05.M

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




PENDEL ARMATUREN SUSPENDED LUMINAIRES



- Opties:**
- Vlees, Brood of Crisp white
 - 2700k of 3500k

- Opties:**
- Meat, Bread or Crisp white
 - 2700k or 3500k



62020WPNS.00-M
5w 3000k 620lm
ηLB 100%