

Marici 205-190 SPECULAR SUSPENDED



Extreem krachtige ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<19). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer brede bundel (>83,0°) en hoge efficiency (max 149lm/w) met **CRI>93**. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Powerful round suspended LED downlight. High gloss aluminium reflector (99,9%) with specular finish (UGR<19). Extra wide beam angle (>83,0°) and high efficiency (max 149lm/w) with **CRI>93**. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy. High color consistency SDCM <2. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali-2 Dali-2	Casambi Casambi
5w	3000k	702	>93	150	3,0	1/3	62020WPNS.00	62020WPNS.01	62020WPNS.02	62020WPNS.05
8w	3000k	1165	>93	250	3,0	1/3	62020WPN.00	62020WPN.01	62020WPN.02	62020WPN.05
12w	3000k	1616	>93	350	3,0	1/3	62006WPN.00	62006WPN.01	62006WPN.02	62006WPN.05
17w	3000k	2274	>93	500	3,0	1/3	62017WPN.00	62017WPN.01	62017WPN.02	62017WPN.05
25w	3000k	3109	>93	700	3,0	1/3	62010WPN.00	62010WPN.01	62010WPN.02	62010WPN.05
33w	3000k	3900	>93	900	3,0	1/3	62015WPN.00	62015WPN.01	62015WPN.02	62015WPN.05

5w	4000k	702	>93	150	3,0	1/3	62021WPNS.00	62021WPNS.01	62021WPNS.02	62021WPNS.05
8w	4000k	1165	>93	250	3,0	1/3	62021WPN.00	62021WPN.01	62021WPN.02	62021WPN.05
12w	4000k	1616	>93	350	3,0	1/3	62007WPN.00	62007WPN.01	62007WPN.02	62007WPN.05
17w	4000k	2274	>93	500	3,0	1/3	62018WPN.00	62018WPN.01	62018WPN.02	62018WPN.05
25w	4000k	3109	>93	700	3,0	1/3	62012WPN.00	62012WPN.01	62012WPN.02	62012WPN.05
33w	4000k	3900	>93	900	3,0	1/3	62016WPN.00	62016WPN.01	62016WPN.02	62016WPN.05

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




PENDEL ARMATUREN SUSPENDED LUMINAIRES



- Opties:**
- Vlees, Brood of Crisp white
 - 2700k of 3500k

- Opties:**
- Meat, Bread or Crisp white
 - 2700k or 3500k



62020WPNS.00
5w 3000k 702lm
ηLB 100%