Marici 205-190 SPECULAR SUSPENDED

Extreem krachtige ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<19). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer brede bundel (>83,0°) en hoge efficiency (max 149lm/w) met **CRI>93 (R9>83)**. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (L90B10 180.000 uur). Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Powerful round suspended LED downlight. High gloss aluminium reflector (99,9%) with specular finish (UGR<19). Extra wide beam angle (>83,0°) and high efficiency (max 149lm/w) with ***CRI>93 (R9>83)****. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy (L90B10 180.000 hours). High color consistency SDCM <2. Five years warranty.*

Wattage *Watts*	**Kleur** *Colour*	**Lumen*** *Lumen**	**CRI** *CRI*	**Amperage (mA)** *Amperage (mA)*	**Gewicht (kg)** *Weight (kg)*	**Noodvoorz. (u)** *Emergency (h)*	**Artikel nr.** *Article no.*	**Dimbaar (1-10V)** *Dimmable (1-10V)*	**Dali-2** *Dali-2*	**Casambi** *Casambi*
5w	3000k	702	>93	150	3,0	1/3	62020WPNS.00	62020WPNS.01	62020WPNS.02	62020WPNS.05
8w	3000k	1165	>93	250	3,0	1/3	62020WPN.00	62020WPN.01	62020WPN.02	62020WPN.05
12w	3000k	1616	>93	350	3,0	1/3	62006WPN.00	62006WPN.01	62006WPN.02	62006WPN.05
17w	3000k	2274	>93	500	3,0	1/3	62017WPN.00	62017WPN.01	62017WPN.02	62017WPN.05
25w	3000k	3109	>93	700	3,0	1/3	62010WPN.00	62010WPN.01	62010WPN.02	62010WPN.05
33w	3000k	3900	>93	900	3,0	1/3	62015WPN.00	62015WPN.01	62015WPN.02	62015WPN.05
5w	4000k	702	>93	150	3,0	1/3	62021WPNS.00	62021WPNS.01	62021WPNS.02	62021WPNS.05
8w	4000k	1165	>93	250	3,0	1/3	62021WPN.00	62021WPN.01	62021WPN.02	62021WPN.05
12w	4000k	1616	>93	350	3,0	1/3	62007WPN.00	62007WPN.01	62007WPN.02	62007WPN.05
17w	4000k	2274	>93	500	3,0	1/3	62018WPN.00	62018WPN.01	62018WPN.02	62018WPN.05
25w	4000k	3109	>93	700	3,0	1/3	62012WPN.00	62012WPN.01	62012WPN.02	62012WPN.05
33w	4000k	3900	>93	900	3,0	1/3	62016WPN.00	62016WPN.01	62016WPN.02	62016WPN.05

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*









Opties:
- Vlees, Brood of Crisp white
- 2700k of 3500k

Opties:
- *Meat, Bread or Crisp white*
- *2700k or 3500k*



62020WPNS.00
5w 3000k 702lm
ηLB 100%

melis lighting