


Extreem krachtige ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<19). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer brede bundel (>83,0°) en hoge efficiency (max 135lm/w) met CRI>80. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Powerful round suspended LED downlight. High gloss aluminium reflector (99,9%) with specular finish (UGR<19). Extra wide beam angle (>83,0°) and high efficiency (max 135lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
9w	3000k	1215	250	2,8	1	62020WPN.00	62020WPN.01	62020WPN.02	62020WPN.05
12w	3000k	1690	350	2,8	1	62006WPN.00	62006WPN.01	62006WPN.02	62006WPN.05
18w	3000k	2370	500	2,8	1	62017WPN.00	62017WPN.01	62017WPN.02	62017WPN.05
25w	3000k	3235	700	2,8	1	62010WPN.00	62010WPN.01	62010WPN.02	62010WPN.05
33w	3000k	4045	900	2,8	1	62015WPN.00	62015WPN.01	62015WPN.02	62015WPN.05
9w	4000k	1280	250	2,8	1	62021WPN.00	62021WPN.01	62021WPN.02	62021WPN.05
12w	4000k	1780	350	2,8	1	62007WPN.00	62007WPN.01	62007WPN.02	62007WPN.05
18w	4000k	2490	500	2,8	1	62018WPN.00	62018WPN.01	62018WPN.02	62018WPN.05
25w	4000k	3395	700	2,8	1	62012WPN.00	62012WPN.01	62012WPN.02	62012WPN.05
33w	4000k	4250	900	2,8	1	62016WPN.00	62016WPN.01	62016WPN.02	62016WPN.05

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



Opties:


- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI

Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren)
Life expectancy (hours)

Watt	L90B10
9	79.000
12	78.000
18	70.000
25	64.000
33	57.000



62006WPN.00

12w 3000k 1690lm
ηLB 80,0%