Marici 205-190 WHITE SUSPENDED

Extreem krachtige ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) witte reflector (UGR<18). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer brede bundel (>73,0°) en hoge efficiency (max 138lm/w) met **CRI>93 (R9>83)**. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen. kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (L90B10 180.000 uur). Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Powerful round suspended LED downlight. High gloss aluminium reflector (99,9%) with white finish (UGR<18). Extra wide beam angle (>73,0°) and high efficiency (max 138lm/w) with **CRI>93 (R9>83)**. *Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy (L90B10 180.000 hours). High color consistency SDCM <2. Five years warranty.*

Wattage Watts	**Kleur** Colour	**Lumen*** Lumen*	**Amperage (mA)** Amperage (mA)	**kg** kg	**Noodvoorz. (u)** Emergency (h)	**Artikel nr.** Article no.	**Dimbaar (1-10V)** Dimmable (1-10V)	**Dali-2** Dali-2	**Casambi** Casambi
5w	3000k	654	150	3,0	1	62020WPNS.00-W	62020WPNS.01-W	62020WPNS.02-W	62020WPNS.05-W
8w	3000k	1086	250	3,0	1	62020WPN.00-W	62020WPN.01-W	62020WPN.02-W	62020WPN.05-W
12w	3000k	1506	350	3,0	1	62006WPN.00-W	62006WPN.01-W	62006WPN.02-W	62006WPN.05-W
17w	3000k	2119	500	3,0	1	62017WPN.00-W	62017WPN.01-W	62017WPN.02-W	62017WPN.05-W
25w	3000k	2896	700	3,0	1	62010WPN.00-W	62010WPN.01-W	62010WPN.02-W	62010WPN.05-W
33w	3000k	3634	900	3,0	1	62015WPN.00-W	62015WPN.01-W	62015WPN.02-W	62015WPN.05-W
5w	4000k	654	150	3,0	1	62021WPNS.00-W	62021WPNS.01-W	62021WPNS.02-W	62021WPNS.05-W
8w	4000k	1086	250	3,0	1	62021WPN.00-W	62021WPN.01-W	62021WPN.02-W	62021WPN.05-W
12w	4000k	1506	350	3,0	1	62007WPN.00-W	62007WPN.01-W	62007WPN.02-W	62007WPN.05-W
17w	4000k	2119	500	3,0	1	62018WPN.00-W	62018WPN.01-W	62018WPN.02-W	62018WPN.05-W
25w	4000k	2896	700	3,0	1	62012WPN.00-W	62012WPN.01-W	62012WPN.02-W	62012WPN.05-W
33w	4000k	3634	900	3,0	1	62016WPN.00-W	62016WPN.01-W	62016WPN.02-W	62016WPN.05-W

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*









Opties:
- Vlees, Brood of Crisp white
- 2700k of 3500k

Opties:
- *Meat, Bread or Crisp white*
- *2700k or 3500k*



62020WPNS.00-W
5w 3000k 654lm
ηLB 100%

melis lighting