Marici 205-190 Specular Track TW

PF>0,95 IP43

Tunable White


Tunable white LED downlight met adapter voor 3-fase rail systemen. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector en gesatineerde PS Microprisma afscherming. Tunable white - dynamisch mengen van licht kleur tussen 2700K en 6500K **(CRI>93, R9>83)**. Zeer geschikt als basis verlichting in gangen of kantoren. Brede bundel (>83°) en lage verblinding op maximaal vermogen (UGR<19). Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne DALI DT8 driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (L90B10 125.000 uur). Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Tunable white LED downlight with adapter for 3-phase track systems. High gloss aluminium reflector (99,9%) with specular finish and satinated PS Microprism diffuser. Tunable white - dynamic mixing of light colour, linear colour mixing between 2700K and 6500K ***(CRI>93, R9>83)****. Wide beam angle (>83°) and low glare at maximum power (UGR<19). White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal DALI DT8 driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (L90B10 125.000 hours). High color consistency SDCM <2. Five years warranty.*

Wattage *Watts*	**Kleur** *Colour*	**Lumen*** *Lumen**	**CRI** *CRI*	**Gewicht (kg)** *Weight (kg)*	**Dali-2** *Dali-2*	**Casambi** *Casambi*
12w	2700-6500k	1433-1524	>93	2,8	62006WT.12.TW	62006WT.12.TWC
18w	2700-6500k	2011-2139	>93	2,8	62006WT.18.TW	62006WT.18.TWC
26w	2700-6500k	2950-3138	>93	2,8	62006WT.26.TW	62006WT.26.TWC
34w	2700-6500k	3544-3770	>93	2,8	62006WT.34.TW	62006WT.34.TWC

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*







TRACK SYSTEEM *TRACK SYSTEM*




Accessoires:
- 3-fase rails en connectors

Opties:
- Vlees, Brood of Crisp white (2700k, 3000k of 3500k)
- 90CRI of 97CRI

Accessories:
- *3-phase tracks and connectors*

Opties:
- *Meat, Bread or Crisp white*
- *(2700k, 3000k or 3500k)*
- *90CRI or 97CRI*



62006WT.12.TW
12w 2700-6500K 1433-1524lm
ηLB 100%

melis lighting