

Marici 205-190 Specular Track




Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van hoogwaardige aluminium (99,9%) hoogglans reflector (UGR<19). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (>83,0°) en hoge efficiency (max 149lm/w) met CRI>93 (R9>83). Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Onderhoudsarm en hoge levensduurverwachting. Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Round LED downlight with adapter for 3-phase track systems. High gloss aluminium reflector (99,9%) with specular finish (UGR<19). Extra wide beam angle (>83,0°) and high efficiency (max 149lm/w) with CRI>93 (R9>83). Satinated PS Microprism diffuser for high comfort. White painted steel (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to mains. Low maintenance and high life expectancy. High color consistency SDCM <2. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali-2 Dali-2	Casambi Casambi
5w	3000k	702	>93	150	2,8	1/3	62020WTS.00	62020WTS.01	62020WTS.02	62020WTS.05
8w	3000k	1165	>93	250	2,8	1/3	62020WT.00	62020WT.01	62020WT.02	62020WT.05
12w	3000k	1616	>93	350	2,8	1/3	62006WT.00	62006WT.01	62006WT.02	62006WT.05
17w	3000k	2274	>93	500	2,8	1/3	62017WT.00	62017WT.01	62017WT.02	62017WT.05
25w	3000k	3109	>93	700	2,8	1/3	62010WT.00	62010WT.01	62010WT.02	62010WT.05
33w	3000k	3900	>93	900	2,8	1/3	62015WT.00	62015WT.01	62015WT.02	62015WT.05
5w	4000k	702	>93	150	2,8	1/3	62021WTS.00	62021WTS.01	62021WTS.02	62021WTS.05
8w	4000k	1165	>93	250	2,8	1/3	62021WT.00	62021WT.01	62021WT.02	62021WT.05
12w	4000k	1616	>93	350	2,8	1/3	62007WT.00	62007WT.01	62007WT.02	62007WT.05
17w	4000k	2274	>93	500	2,8	1/3	62018WT.00	62018WT.01	62018WT.02	62018WT.05
25w	4000k	3109	>93	700	2,8	1/3	62012WT.00	62012WT.01	62012WT.02	62012WT.05
33w	4000k	3900	>93	900	2,8	1/3	62016WT.00	62016WT.01	62016WT.02	62016WT.05

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



TRACK SYSTEEM TRACK SYSTEM




Accessoires:
- 3-fase rails en connectors

Opties:
- Vlees, Brood of Crisp white
(2700k, 3000k of 3500k)

Accessories:
- 3-phase tracks and connectors

Opties:
- Meat, Bread or Crisp white
- (2700k, 3000k or 3500k)



62020WTS.00
5w 702lm 3000K
ηLB 100%

melis lighting