

Marici 205-190 Specular Track




Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van hoogwaardige aluminium (99,9%) hoogglans reflector (UGR<19). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (>83,0°) en hoge efficiency (max 135lm/w) met CRI>80. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with adapter for 3-phase track systems. High gloss aluminium reflector (99,9%) with specular finish (UGR<19). Extra wide beam angle (>83,0°) and high efficiency (max 135lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to mains. Low maintenance and high life expectancy. Color stability, Mac Adam <3. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dali Dali	Casambi Casambi
9w	3000k	1215	250	2,8	1	62020WT.00	62020WT.02	62020WT.05
12w	3000k	1690	350	2,8	1	62006WT.00	62006WT.02	62006WT.05
18w	3000k	2370	500	2,8	1	62017WT.00	62017WT.02	62017WT.05
25w	3000k	3235	700	2,8	1	62010WT.00	62010WT.02	62010WT.05
33w	3000k	4045	900	2,8	1	62015WT.00	62015WT.02	62015WT.05
9w	4000k	1280	250	2,8	1	62021WT.00	62021WT.02	62021WT.05
12w	4000k	1780	350	2,8	1	62007WT.00	62007WT.02	62007WT.05
18w	4000k	2490	500	2,8	1	62018WT.00	62018WT.02	62018WT.05
25w	4000k	3395	700	2,8	1	62012WT.00	62012WT.02	62012WT.05
33w	4000k	4250	900	2,8	1	62016WT.00	62016WT.02	62016WT.05

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



TRACK SYSTEEM TRACK SYSTEM



Accessoires:

- 3-fase rails en connectors

Opties:

- Vlees, Brood of Crisp white (2700k, 3000k of 3500k)
- 90CRI of 97CRI


Accessories:

- 3-phase tracks and connectors

Opties:

- Meat, Bread or Crisp white
- (2700k, 3000k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
9	79.000
12	78.000
18	70.000
25	64.000
33	57.000



62007WT.00

12w 1780lm 4000K
ηLB 80%

melis lighting