Marici 205-190 White Track TW

PF>0,95 IP43

Tunable White

Tunable white LED downlight met adapter voor 3-fase rail systemen. Voorzien van decoratieve aluminium (99,9%) witte reflector en gesatineerde PS Microprisma afscherming. Tunable white - dynamisch mengen van licht kleur tussen 2700K en 6500K **(CRI>93, R9>83)**. Zeer geschikt als basis verlichting in gangen of kantoren. Brede bundel (>73°) en lage verblinding op maximaal vermogen (UGR<18). Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne DALI DT8 driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (L90B10 125.000 uur). Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Tunable white LED downlight with adapter for 3-phase track systems. High gloss aluminium reflector (99,9%) with white finish and satinated PS Microprism diffuser. Tunable white - dynamic mixing of light colour, linear colour mixing between 2700K and 6500K **(CRI>93, R9>83)**. *Wide beam angle (>73°) and low glare at maximum power (UGR<18). White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal DALI DT8 driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (L90B10 125.000 hours). High color consistency SDCM <2. Five years warranty.*

Wattage Watts	**Kleur** Colour	**Lumen*** Lumen*	**CRI** CRI	**Gewicht (kg)** Weight (kg)	**Dali-2** Dali-2	**Casambi** Casambi
12w	2700-6500k	1346-1435	>93	2,8	62006WT.12.TWW	62006WT.12.TWWC
18w	2700-6500k	1889-2014	>93	2,8	62006WT.18.TWW	62006WT.18.TWWC
26w	2700-6500k	2772-2955	>93	2,8	62006WT.26.TWW	62006WT.26.TWWC
34w	2700-6500k	3329-3549	>93	2,8	62006WT.34.TWW	62006WT.34.TWWC

* Lichtstroom van armatuur, tolerantie van +/- 10%

** Luminaire luminous flux, tolerance of +/- 10%*







TRACK SYSTEEM *TRACK SYSTEM*



Accessoires:
- 3-fase rails en connectors

Opties:
- Vlees, Brood of Crisp white (2700k, 3000k of 3500k)
- 90CRI of 97CRI

Accessories:
- *3-phase tracks and connectors*

Opties:
- *Meat, Bread or Crisp white*
- *(2700k, 3000k or 3500k)*
- *90CRI or 97CRI*



62006WT.12.TWW
12w 2700-6500K 1346-1435lm
ηLB 100%

melis lighting