

Marici 205-190 White Track TW




Tunable white LED downlight met adapter voor 3-fase rail systemen. Voorzien van decoratieve aluminium (99,9%) witte reflector en gesatineerde PS Microprisma afscherming. Tunable white - dynamisch mengen van licht kleur tussen 2700K en 6500K (CRI>92). Zeer geschikt als basis verlichting in gangen of kantoren. Brede bundel (>73°) en lage verblinding op maximaal vermogen (UGR<18). Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne DALI DT8 driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (60.000 uur L90B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Tunable white LED downlight with adapter for 3-phase track systems. High gloss aluminium reflector (99,9%) with white finish and satinated PS Microprism diffuser. Tunable white - dynamic mixing of light colour, linear colour mixing between 2700K and 6500K (CRI>92). Wide beam angle (>73°) and low glare at maximum power (UGR<18). White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal DALI DT8 driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (60.000 hours L90B10). Colour stability, Mac Adam <3. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Dali Dali	Casambi Casambi
13w	2700-6500k	1150-1340	250	2,8	62006WT.13W.TW	62006WT13W.TWC
19w	2700-6500k	1570-1835	350	2,8	62006WT.19W.TW	62006WT19W.TWC
27w	2700-6500k	2220-2615	500	2,8	62006WT.27W.TW	62006WT27W.TWC
32w	2700-6500k	2680-3080	600	2,8	62006WT.32W.TW	62006WT32W.TWC

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



TRACK SYSTEEM TRACK SYSTEM



Accessoires:

- 3-fase rails en connectors

Opties:


- Vlees, Brood of Crisp white (2700k, 3000k of 3500k)
- 90CRI of 97CRI

Accessories:

- 3-phase tracks and connectors

Opties:

- Meat, Bread or Crisp white (2700k, 3000k or 3500k)
- 90CRI or 97CRI



62006WT.13W.TW
13w 2700-6500K 1150-1340lm
ηLB 74%