Marici 205-190 White Track

PF>0,95 IP43


Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van hoogwaardige aluminium (99,9%) witte reflector (UGR<18). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (>73,0°) en hoge efficiency (max 125lm/w) met CRI>80. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with adapter for 3-phase track systems. High gloss aluminium reflector (99,9%) with white finish (UGR<18). Extra wide beam angle (>73,0°) and high efficiency (max 125lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to mains. Low maintenance and high life expectancy. Color stability, Mac Adam <3. Five years warranty.

Wattage *Watts*	**Kleur** *Colour*	**Lumen*** *Lumen**	**Amperage (mA)** *Amperage (mA)*	**kg** *kg*	**Noodvoorz. (u)** *Emergency (h)*	**Artikel nr.** *Article no.*	**Dali** *Dali*	**Casambi** *Casambi*
9w	3000k	1125	250	2,8	1	62020WT.00-W	62020WT.02-W	62020WT.05-W
12w	3000k	1565	350	2,8	1	62006WT.00-W	62006WT.02-W	62006WT.05-W
18w	3000k	2190	500	2,8	1	62017WT.00-W	62017WT.02-W	62017WT.05-W
25w	3000k	2990	700	2,8	1	62010WT.00-W	62010WT.02-W	62010WT.05-W
33w	3000k	3740	900	2,8	1	62015WT.00-W	62015WT.02-W	62015WT.05-W
9w	4000k	1185	250	2,8	1	62021WT.00-W	62021WT.02-W	62021WT.05-W
12w	4000k	1645	350	2,8	1	62007WT.00-W	62007WT.02-W	62007WT.05-W
18w	4000k	2300	500	2,8	1	62018WT.00-W	62018WT.02-W	62018WT.05-W
25w	4000k	3140	700	2,8	1	62012WT.00-W	62012WT.02-W	62012WT.03-W
33w	4000k	3920	900	2,8	1	62016WT.00-W	62016WT.02-W	62016WT.03-W

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*





TRACK SYSTEEM *TRACK SYSTEM*




Accessoires:
- 3-fase rails en connectors

Opties:
- Vlees, Brood of Crisp white (2700k, 3000k of 3500k)
- 90CRI of 97CRI

Accessories:
- 3-phase tracks and connectors

Opties:
- Meat, Bread or Crisp white
- (2700k, 3000k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren) *Life expectancy (hours)*	
Watt	**L90B10**
9	79.000
12	78.000
18	70.000
25	64.000
33	57.000



62007WT.00-W
12w 4000K 1645lm
ηLB 74%

melis lighting