

Marici 205-190 Wallwasher Specular



Ronde LED wallwasher opbouw downlight. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<19). Zeer brede bundel (83,0°) en hoge efficiency (max 135lm/w) met CRI>80. Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver met mogelijkheid tot doorlussen. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round surface mounted LED wallwasher downlight. High gloss aluminium reflector (99,9%) (UGR<19) with specular finish. Extra wide beam angle (83,0°) and high efficiency (max 135lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver with possibility for through-wiring. Direct connection to 220-240VAC. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali	Casambi
9w	3000k	1215	250	2,8	1	62020WPB.00.WS	62020WPB.01.WS	62020WPB.02.WS	62020WPB.05.WS
12w	3000k	1690	350	2,8	1	62006WPB.00.WS	62006WPB.01.WS	62006WPB.02.WS	62006WPB.05.WS
18w	3000k	2370	500	2,8	1	62017WPB.00.WS	62017WPB.01.WS	62017WPB.02.WS	62017WPB.05.WS
25w	3000k	3235	700	2,8	1	62010WPB.00.WS	62010WPB.01.WS	62010WPB.02.WS	62010WPB.05.WS
33w	3000k	4045	900	2,8	1	62015WPB.00.WS	62015WPB.01.WS	62015WPB.02.WS	62015WPB.05.WS
9w	4000k	1280	250	2,8	1	62021WPB.00.WS	62021WPB.01.WS	62021WPB.02.WS	62021WPB.05.WS
12w	4000k	1780	350	2,8	1	62007WPB.00.WS	62007WPB.01.WS	62007WPB.02.WS	62007WPB.05.WS
18w	4000k	2490	500	2,8	1	62018WPB.00.WS	62018WPB.01.WS	62018WPB.02.WS	62018WPB.05.WS
25w	4000k	3395	700	2,8	1	62012WPB.00.WS	62012WPB.01.WS	62012WPB.02.WS	62012WPB.05.WS
33w	4000k	4250	900	2,8	1	62016WPB.00.WS	62016WPB.01.WS	62016WPB.02.WS	62016WPB.05.WS

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



OPBOUW DOWNLIGHTS SURFACE MOUNTED DOWNLIGHTS




Opties:

- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI
- Schuinstelling voor aflopende plafonds op aanvraag
- Andere RAL kleur

Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI
- Diagonal attachment for sloped ceilings on request
- Different RAL Colour

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
9	79.000
12	78.000
18	70.000
25	64.000
33	57.000



62006WPB.00.WS
12w 3000k 1690lm
ηLB 80,0%

melis lighting