

Marici 205-190 White RGB-TW



RGB en Tunable white LED opbouw downlight met gesatineerde PS Microprisma afscherming. Brede bundel (>73°) en lage verblinding op maximaal vermogen (UGR<18). Witte aluminium reflector. Voorzien van dimbaar RGB + tunable white LED technology (>100lm/w, 2500-7000k, CRI>90). Aanstuurbaar via DALI DT8 (slecht 1 BUS adres). RGB dimming 0-100%, CCT dimming 5-100%. Wit gelakte (RAL 9003) aluminium behuizing. Zeer geschikt als basis verlichting in scholen, theaters en musea. Inclusief DALI driver. Directe aansluiting op 48VDC of 220-240VAC. Zeer hoge initiële kleurstabiliteit Mac Adam <1. Snelle en eenvoudige montage met veren. Onderhoudsvrij en hoge levensduurverwachting (50.000 uur L90B10). Vijf jaar garantie.

RGB and tunable white modular surface mounted LED downlight with a satinated PS Microprism diffuser. Wide beam angle (>73°) and low glare at maximum power (UGR<18). White aluminum reflector. Build-in RGB + tuneable white LED technology (>100lm/w, 2500-7000k, CRI>90). RGB dimming 0-100%, CCT dimming 5-100%. Controllable over DALI DT8 protocol (only 1 bus adress per luminaire). White painted aluminum die cast body (RAL9003). Ideal for schools, museums, theaters and hospitals. Delivered including DALI driver. Direct connection to 48VDC or 220-240VAC. Very high initial colour stability, Mac Adam <1. Low maintenance and high life expectancy (50.000 hours L90B10). Fast and easy mounting with springs. Five years warranty.

Wattage Watts	Lumen* Lumen*	CRI CRI	Gewicht (kg) Weight (kg)	48VDC 48VDC	220-240VAC 220-240VAC	Casambi Casambi
22w	1700	>90	2,8	62009WPB.22D.RGBW	62009WPB.22A.RGBW	62009WPB.22C.RGBW
31w	2220	>90	2,8	62009WPB.31D.RGBW	62009WPB.31A.RGBW	62009WPB.31C.RGBW

* Lichtstroom van armatuur, tolerantie van +/- 10%


* Luminaire luminous flux, tolerance of +/- 10%



OPBOUW DOWNLIGHTS
SURFACE MOUNTED DOWNLIGHTS



- Opties:**
- Schuinstelling voor aflopende plafonds op aanvraag
 - Andere RAL kleur
- Opties:**
- Diagonal attachment for sloped ceilings on request
 - Different RAL Colour



62009WPB.22D.RGBW
22w 1700lm
ηLB 74%