

Marici 240 EasySense Specular





Ronde LED downlight met een lage inbouwhoogte. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<18). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (74,0°) en hoge efficiency (max 149lm/w) met **CRI>93**. Wit gelakte (RAL 9003) aluminium behuizing. Wordt geleverd inclusief externe driver. De EasySense-sensor combineert beweging- en daglichtregeling. Tot 40 sensoren kunnen draadloos worden gegroepeerd. Snelle en eenvoudige montage met veren. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting. Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Round LED downlight with shallow build-in height. High gloss aluminium reflector (99,9%) with specular finish (UGR<18). Extra wide beam angle (74,0°) and high efficiency (max 149lm/w) with **CRI>93**. Satinated PS Microprism diffuser for high comfort. White painted aluminium die cast body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including external driver. The EasySense sensor combines occupancy sensing, daylight harvesting and task tuning. Up to 40 sensors can be grouped wireless. Direct connection to 220-240VAC. Low maintenance and high life expectancy. High color consistency SDCM <2. Fast and easy mounting with springs. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.
5w	3000k	702	>93	150	1,4	1/3	62023W.0530
8w	3000k	1165	>93	250	1,4	1/3	62023W.0830
12w	3000k	1616	>93	350	1,4	1/3	62023W.1230
17w	3000k	2274	>93	500	1,4	1/3	62023W.1730
25w	3000k	3109	>93	700	1,4	1/3	62023W.2530
33w	3000k	3900	>93	900	1,4	1/3	62023W.3330
39w	3000k	4436	>93	1050	1,4	1/3	62023W.3930
5w	4000k	702	>93	150	1,4	1/3	62023W.0540
9w	4000k	1165	>93	250	1,4	1/3	62023W.0940
12w	4000k	1616	>93	350	1,4	1/3	62023W.1240
18w	4000k	2274	>93	500	1,4	1/3	62023W.1840
25w	4000k	3109	>93	700	1,4	1/3	62023W.2540
33w	4000k	3900	>93	900	1,4	1/3	62023W.3340
39w	4000k	4436	>93	1050	1,4	1/3	62023W.3940

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




INBOUW DOWNLIGHTS RECESSED DOWNLIGHTS



- Opties:**
- 1,5 meter snoer met 3-polige Shuko stekker
 - 0,5 meter snoer + GST18i3® connector
 - Andere RAL kleur
 - 2700K, 3500k, 5000k of hogere CRI waarde 90/97
 - Vlees, brood of Crisp White
 - IP65

- Options:**
- 1,5m cable with Shuko 3-pin plug
 - 0,5 meter cable + GST18i3® connector
 - Different RAL color
 - 2700k, 3500k, 5000k or higher CRI values 90/97
 - Meat, bread or Crisp White
 - IP65



62023W.0530
5w 3000k 702lm
ηLB 100%