Optic

PF>0,9 IP65 IK10


Rond LED armatuur voor wand of plafondmontage. Zeer diffuus en krachtig licht met goede kleurweergave (Ra>80). Zeer slagvaste en weerbestendige polycarbonaat behuizing met opalen difuser. Alle elektronische componenten in de behuizing. Aansluiting op voeding via kroonsteen in de behuizing. Invoer voeding via achterzijde van het armatuur met mogelijkheid tot doorlussen. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (65.000 uur L80B20). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED luminaire for wall or ceiling. Diffuse light distribution with good colour rendering (Ra>80). Highly protected against external impacts and waterproof. Housing made of polycarbonate with opal diffuser. All electronic components inside the luminaire. Connection through the back of the luminaire directly to connector block. Suitable for series connection. Low maintenance and high life expectancy (65.000 hours L80B20). Colour stability, Mac Adam <3. Fast and easy mounting with springs. Five years warranty.

Wattage *Watts*	**Ring kleur** *Ring Colour*	**Kleur** *Color*	**Lumen*** *Lumen**	**Gewicht (kg)** *Weight (kg)*	**Noodvoorz. (u)** *Emergency (h)*	**Diameter (mm)** *Diameter (mm)*	**Hoogte (H)** *Height (h)*	**Artikel nr.** *Article no.*	**Bewegingssensor** *Motion sensor*
14w	wit/white	3000k	1410	1,1		340	115	20069W.14.30	20069W.14.30S
18w	wit/white	3000k	1750	1,1	3	340	115	20069W.18.30	20069W.18.30S
25w	wit/white	3000k	2700	1,1	3	340	115	20069W.25.30	20069W.25.30S
30w	wit/white	3000k	3400	1,1		340	115	20069W.30.30	20069W.30.30S
14w	wit/white	4000k	1520	1,1		340	115	20069W.14.40	20069W.14.40S
18w	wit/white	4000k	1900	1,1	3	340	115	20069W.18.40	20069W.18.40S
25w	wit/white	4000k	2900	1,1	3	340	115	20069W.25.40	20069W.25.40S
30w	wit/white	4000k	3700	1,1		340	115	20069W.30.40	20069W.30.40S

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*




WAND EN PLAFOND *WALL AND CEILING*



Opties:
- Geïntegreerde bewegingssensor
- Corridor functie
- Dali

Options:
- *Integrated motionsensor*
- *Corridor function*
- *Dali*



20069W.14.30
14w 3000k 1410lm
ηLB 100%

melis lighting