

Rond LED armatuur met minimalistisch design en directe/indirecte lichtbundel. Behuizing gemaakt van gebogen aluminium profiel. Verkrijgbaar in wit gelakt (RAL 9003) zwart (RAL 9005) of zilver grijs (RAL 9006). Geschikt voor toepassing in onder andere winkelcentra, hotels en kantoren. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED luminaire with minimalistic design and direct/indirect beam angle. Housing made of aluminium profile painted in white (RAL 9003) black (RAL 9005) or silver grey (RAL 9006). Suitable for shopping centres, hotels and offices. Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <3. Warranty 5 years.

Micro Prisma / Micro Prism



Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Diameter (mm) Diameter (mm)	Hoogte (mm) Height (mm)	kg kg	Artikel nr. Article no.	Dali Dali	Casambi Casambi
24w+7w	3000k	2790	>80	400	80	2,5	26019MP_40030	26019MP_40032	26019MP_40035
41w+12w	3000k	4770	>80	600	80	4	26019MP_60030	26019MP_60032	26019MP_60035
65w+20w	3000k	7650	>80	900	80	8	26019MP_90030	26019MP_90032	26019MP_90035
85w+25w	3000k	9900	>80	1200	80	12	26019MP_120030	26019MP_120032	26019MP_120035
105w+32w	3000k	12.330	>80	1500	100	17	26019MP_150030	26019MP_150032	26019MP_150035
140w+42w	3000k	16.380	>80	2000	100	20	26019MP_200030	26019MP_200032	26019MP_200035
180w+54w	3000k	21.060	>80	2500	100	23	26019MP_250030	26019MP_250032	26019MP_250035
220w+66w	3000k	25.740	>80	3000	100	27	26019MP_300030	26019MP_300032	26019MP_300035
350w+105w	3000k	40.950	>80	3500	100	30	26019MP_350030	26019MP_350032	26019MP_350035
24w+7w	4000k	2930	>80	400	80	2,5	26019MP_40040	26019MP_40042	26019MP_40045
41w+12w	4000k	5010	>80	600	80	4	26019MP_60040	26019MP_60042	26019MP_60045
65w+20w	4000k	8030	>80	900	80	8	26019MP_90040	26019MP_90042	26019MP_90045
85w+25w	4000k	10.395	>80	1200	80	12	26019MP_120040	26019MP_120042	26019MP_120045
105w+32w	4000k	12.945	>80	1500	100	17	26019MP_150040	26019MP_150042	26019MP_150045
140w+42w	4000k	17.200	>80	2000	100	20	26019MP_200040	26019MP_200042	26019MP_200045
180w+54w	4000k	22.115	>80	2500	100	23	26019MP_250040	26019MP_250042	26019MP_250045
220w+66w	4000k	27.025	>80	3000	100	27	26019MP_300040	26019MP_300042	26019MP_300045
350w+105w	4000k	43.000	>80	3500	100	30	26019MP_350040	26019MP_350042	26019MP_350045

* Lichtstroom van armatuur, tolerantie van +/- 10%



* Luminaire luminous flux, tolerance of +/- 10%

_ W=wit / B=zwart / G=grijs

_ W=white / B=black / G=grey



Uitsluitend geschikt voor plafondmontage!
Only suitable for ceiling mounting!



26019.MP_40030
 24w+7w 3000k 2790lm
 ηLB 100%

Opaal / Opal

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Diameter (mm) Diameter (mm)	Hoogte (mm) Height (mm)	kg kg	Artikel nr. Article no.	Dali Dali	Casambi Casambi
24w+7w	3000k	2650	>80	400	80	2,5	26019OP_40030	26019OP_40032	26019OP_40035
41w+12w	3000k	4530	>80	600	80	4	26019OP_60030	26019OP_60032	26019OP_60035
65w+20w	3000k	7270	>80	900	80	8	26019OP_90030	26019OP_90032	26019OP_90035
85w+25w	3000k	9405	>80	1200	80	12	26019OP_120030	26019OP_120032	26019OP_120035
105w+32w	3000k	11715	>80	1500	100	17	26019OP_150030	26019OP_150032	26019OP_150035
140w+42w	3000k	15.560	>80	2000	100	20	26019OP_200030	26019OP_200032	26019OP_200035
180w+54w	3000k	18.910	>80	2500	100	23	26019OP_250030	26019OP_250032	26019OP_250035
220w+66w	3000k	24.455	>80	3000	100	27	26019OP_300030	26019OP_300032	26019OP_300035
350w+105w	3000k	38.905	>80	3500	100	30	26019OP_350030	26019OP_350032	26019OP_350035
24w+7w	4000k	2790	>80	400	80	2,5	26019OP_40040	26019OP_40042	26019OP_40045
41w+12w	4000k	4770	>80	600	80	4	26019OP_60040	26019OP_60042	26019OP_60045
65w+20w	4000k	7650	>80	900	80	8	26019OP_90040	26019OP_90042	26019OP_90045
85w+25w	4000k	9900	>80	1200	80	12	26019OP_120040	26019OP_120042	26019OP_120045
105w+32w	4000k	12.330	>80	1500	100	17	26019OP_150040	26019OP_150042	26019OP_150045
140w+42w	4000k	16.380	>80	2000	100	20	26019OP_200040	26019OP_200042	26019OP_200045
180w+54w	4000k	21.060	>80	2500	100	23	26019OP_250040	26019OP_250042	26019OP_250045
220w+66w	4000k	25.740	>80	3000	100	27	26019OP_300040	26019OP_300042	26019OP_300045
350w+105w	4000k	40.950	>80	3500	100	30	26019OP_350040	26019OP_350042	26019OP_350045

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%

_ W=wit / B=zwart / G=grijs

_ W=white / B=black / G=grey