

Performer 570



PENDEL ARMATUREN SUSPENDED LUMINAIRES

Zeer hoogwaardige krachtige high bay met hoge lichtopbrengst. Grijs gelakt stalen behuizing met decoratieve transparante Lexalite® prisma reflector (PMMA) met zeer lage verblinding (UGR<19) en interne soft focus diffuser voor extra comfort. Unieke passieve heatpipe koeling. Hoog rendement COB met medium bundelbreedte (70 graden). Zeer goed toepasbaar als krachtige decoratieve pendel in vides, hallen en showrooms. Onderhoudsarm en hoge levensduurverwachting (60.000 uur L90B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.



Powerful high bay with high light output. Grey painted steel housing with decorative transparent Lexalite® prismatic reflector (PMMA) with low glare (UGR<19) and internal soft focus diffuser for extra comfort. Unique passive heat pipe cooling. Applicable as powerful decorative pendant in high rooms, entrance halls and showrooms. Low maintenance and high life expectancy (60.000 hours L90B10). Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.



Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI (Ra) CRI (Ra)	Graden Degrees	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dali Dali
50w	3000k	7.413	80	70° soft	9	1/3	23005G.50.30.0	23005G.50.30.2
50w	4000k	7.782	80	70° soft	9	1/3	23005G.50.40.0	23005G.50.40.2
100w	3000k	11.685	80	70° soft	9	1/3	23005G.100.30.0	23005G.100.30.2
100w	4000k	12.267	80	70° soft	9	1/3	23005G.100.40.0	23005G.100.40.2
150w	3000k	16.179	80	70° soft	9	1/3	23005G.150.30.0	23005G.150.30.2
150w	4000k	17.040	80	70° soft	9	1/3	23005G.150.40.0	23005G.150.40.2
195w	3000k	19.270	80	70° soft	9	1/3	23005G.195.30.0	23005G.195.30.2
195w	4000k	20.229	80	70° soft	9	1/3	23005G.195.40.0	23005G.195.40.2

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



23005G.50.30.0
50w 3000k 7.413lm
ηLB 81%

melis lighting