Plane BLACK UP/DOWN SUSPENDED

Elegant en slank LED pendel armatuur met directe/indirecte lichtbundel. Behuizing gemaakt van geëxtrudeerd aluminium. Voorzien van breedstralende (>94°) hoogwaardig Micro Prisma diffuser (UGR<19). Geschikt voor o.a. scholen, kantoren, recepties en galerieën. Alle elektronische componenten in de behuizing. Wordt geleverd inclusief pendel accessoires: staalkabels (3m) en snoer (3,5m). Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.


Elegant and slim suspended LED luminaire with direct/indirect beam angle. Housing made out of extruded aluminium. Equipped with high quality wide angle (>94°) Micro Prisma diffuser (UGR<19). Suitable for schools, offices, reception areas, and galleries. All electronic components inside the housing. Delivered including pendant suspension, steel cables (3m) and mains cable (3,5m). Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <3. Warranty 5 years.

Micro Prisma / *Micro Prism*

Wattage *Watts*	**Kleur** *Colour*	**Lumen*** *Lumen**	**L (mm)** *L (mm)*	**B (mm)** *W (mm)*	**H (mm)** *H (mm)*	**kg** *kg*	**Noodvoorz. (u)** *Emergency (h)*	**Artikel nr.** *Article no.*	**Dali** *Dali*	**EasySense** *EasySense*
14w+13w	3000k	1400+1300	600	50	59	0,9	1/3	61018BM.1430DI	61018BM.1432DI	61018BM.1437DI
20w+13w	3000k	2000+1300	600	50	59	0,9	1/3	61018BM.2030DI	61018BM.2032DI	61018BM.2037DI
21w+20w	3000k	2100+2000	900	50	59	1,3	1/3	61018BM.2130DI	61018BM.2132DI	61018BM.2137DI
30w+20w	3000k	3000+2000	900	50	59	1,3	1/3	61018BM.3030DI	61018BM.3032DI	61018BM.3037DI
27w+26w	3000k	2700+2600	1200	50	59	1,7	1/3	61018BM.2730DI	61018BM.2732DI	61018BM.2737DI
39w+26w	3000k	3900+2600	1200	50	59	1,7	1/3	61018BM.3930DI	61018BM.3932DI	61018BM.3937DI
34w+32w	3000k	3400+3200	1500	50	59	2,1	1/3	61018BM.3430DI	61018BM.3432DI	61018BM.3437DI
49w+32w	3000k	4900+3200	1500	50	59	2,1	1/3	61018BM.4930DI	61018BM.4932DI	61018BM.4937DI
41w+38w	3000k	4100+3800	1800	50	59	2,5	1/3	61018BM.4130DI	61018BM.4132DI	61018BM.4137DI
59w+38w	3000k	5900+3800	1800	50	59	2,5	1/3	61018BM.5930DI	61018BM.5932DI	61018BM.5937DI
48w+44w	3000k	4800+4400	2100	50	59	3,0	1/3	61018BM.4830DI	61018BM.4832DI	61018BM.4837DI
69w+44w	3000k	6900+4400	2100	50	59	3,0	1/3	61018BM.6930DI	61018BM.6932DI	61018BM.6937DI
55w+50w	3000k	5500+5000	2400	50	59	3,4	1/3	61018BM.5530DI	61018BM.5532DI	61018BM.5537DI
79w+50w	3000k	7900+5000	2400	50	59	3,4	1/3	61018BM.7930DI	61018BM.7932DI	61018BM.7937DI
14w+13w	4000k	1470+1365	600	50	59	0,9	1/3	61018BM.1440DI	61018BM.1442DI	61018BM.1447DI
20w+13w	4000k	2100+1365	600	50	59	0,9	1/3	61018BM.2040DI	61018BM.2042DI	61018BM.2047DI
21w+20w	4000k	2210+2100	900	50	59	1,3	1/3	61018BM.2140DI	61018BM.2142DI	61018BM.2147DI
30w+20w	4000k	3155+2100	900	50	59	1,3	1/3	61018BM.3040DI	61018BM.3042DI	61018BM.3047DI
27w+26w	4000k	2840+2730	1200	50	59	1,7	1/3	61018BM.2740DI	61018BM.2742DI	61018BM.2747DI
39w+26w	4000k	4100+2730	1200	50	59	1,7	1/3	61018BM.3940DI	61018BM.3942DI	61018BM.3947DI
34w+32w	4000k	3575+3360	1500	50	59	2,1	1/3	61018BM.3440DI	61018BM.3442DI	61018BM.3447DI
49w+32w	4000k	5150+3360	1500	50	59	2,1	1/3	61018BM.4940DI	61018BM.4942DI	61018BM.4947DI
41w+38w	4000k	4310+3990	1800	50	59	2,5	1/3	61018BM.4140DI	61018BM.4142DI	61018BM.4147DI
59w+38w	4000k	6200+3990	1800	50	59	2,5	1/3	61018BM.5940DI	61018BM.5942DI	61018BM.5947DI
48w+44w	4000k	5045+4620	2100	50	59	3,0	1/3	61018BM.4840DI	61018BM.4842DI	61018BM.4847DI
69w+44w	4000k	8055+4620	2100	50	59	3,0	1/3	61018BM.6940DI	61018BM.6942DI	61018BM.6947DI
55w+50w	4000k	5780+5250	2400	50	59	3,4	1/3	61018BM.5540DI	61018BM.5542DI	61018BM.5547DI
79w+50w	4000k	8305+5250	2400	50	59	3,4	1/3	61018BM.7940DI	61018BM.7942DI	61018BM.7947DI

* Lichtstroom van armatuur, tolerantie van +/- 10%

** Luminaire luminous flux, tolerance of +/- 10%*






Opties:
- Geïntegreerde bewegingssensor
- Corridor functie
- EasySense-sensor

Options:
- *Integrated motionsensor*
- *Corridor function*
- *EasySense-sensor*





61018BM.1430DI
14w+13w 3000k 1400+1300lm
ηLB 100%

melis lighting

Plane BLACK UP/DOWN SUSPENDED

Opaal / *Opal*

Wattage Watts	**Kleur** Colour	**Lumen*** Lumen*	**L (mm)** L (mm)	**B (mm)** W (mm)	**H (mm)** H (mm)	**kg** kg	**Noodvoorz. (u)** Emergency (h)	**Artikel nr.** Article no.	**Dali** Dali	**EasySense** EasySense
14w+13w	3000k	1330+1265	600	50	59	0,9	1/3	61018BP.1430DI	61018BP.1432DI	61018BP.1437DI
20w+13w	3000k	1900+1265	600	50	59	0,9	1/3	61018BP.2030DI	61018BP.2032DI	61018BP.2037DI
21w+20w	3000k	1955+1900	900	50	59	1,3	1/3	61018BP.2130DI	61018BP.2132DI	61018BP.2137DI
30w+20w	3000k	2850+1900	900	50	59	1,3	1/3	61018BP.3030DI	61018BP.3032DI	61018BP.3037DI
27w+26w	3000k	2565+2470	1200	50	59	1,7	1/3	61018BP.2730DI	61018BP.2732DI	61018BP.2737DI
39w+26w	3000k	3705+2470	1200	50	59	1,7	1/3	61018BP.3930DI	61018BP.3932DI	61018BP.3937DI
34w+32w	3000k	3230+3040	1500	50	59	2,1	1/3	61018BP.3430DI	61018BP.3432DI	61018BP.3437DI
49w+32w	3000k	4655+3040	1500	50	59	2,1	1/3	61018BP.4930DI	61018BP.4932DI	61018BP.4937DI
41w+38w	3000k	3895+3610	1800	50	59	2,5	1/3	61018BP.4130DI	61018BP.4132DI	61018BP.4137DI
59w+38w	3000k	5605+3610	1800	50	59	2,5	1/3	61018BP.5930DI	61018BP.5932DI	61018BP.5937DI
48w+44w	3000k	4560+4180	2100	50	59	3,0	1/3	61018BP.4830DI	61018BP.4832DI	61018BP.4837DI
69w+44w	3000k	6555+4180	2100	50	59	3,0	1/3	61018BP.6930DI	61018BP.6932DI	61018BP.6937DI
55w+50w	3000k	5225+4750	2400	50	59	3,4	1/3	61018BP.5530DI	61018BP.5532DI	61018BP.5537DI
79w+50w	3000k	7505+4750	2400	50	59	3,4	1/3	61018BP.7930DI	61018BP.7932DI	61018BP.7937DI
14w+13w	4000k	1400+1300	600	50	59	0,9	1/3	61018BP.1440DI	61018BP.1442DI	61018BP.1447DI
20w+13w	4000k	2000+1300	600	50	59	0,9	1/3	61018BP.2040DI	61018BP.2042DI	61018BP.2047DI
21w+20w	4000k	2100+2000	900	50	59	1,3	1/3	61018BP.2140DI	61018BP.2142DI	61018BP.2147DI
30w+20w	4000k	3000+2000	900	50	59	1,3	1/3	61018BP.3040DI	61018BP.3042DI	61018BP.3047DI
27w+26w	4000k	2700+2600	1200	50	59	1,7	1/3	61018BP.2740DI	61018BP.2742DI	61018BP.2747DI
39w+26w	4000k	3900+2600	1200	50	59	1,7	1/3	61018BP.3940DI	61018BP.3942DI	61018BP.3947DI
34w+32w	4000k	3400+3200	1500	50	59	2,1	1/3	61018BP.3440DI	61018BP.3442DI	61018BP.3447DI
49w+32w	4000k	4900+3200	1500	50	59	2,1	1/3	61018BP.4940DI	61018BP.4942DI	61018BP.4947DI
41w+38w	4000k	4100+3800	1800	50	59	2,5	1/3	61018BP.4140DI	61018BP.4142DI	61018BP.4147DI
59w+38w	4000k	5900+3800	1800	50	59	2,5	1/3	61018BP.5940DI	61018BP.5942DI	61018BP.5947DI
48w+44w	4000k	4800+4400	2100	50	59	3,0	1/3	61018BP.4840DI	61018BP.4842DI	61018BP.4847DI
69w+44w	4000k	6900+4400	2100	50	59	3,0	1/3	61018BP.6940DI	61018BP.6942DI	61018BP.6947DI
55w+50w	4000k	5500+5000	2400	50	59	3,4	1/3	61018BP.5540DI	61018BP.5542DI	61018BP.5547DI
79w+50w	4000k	7900+5000	2400	50	59	3,4	1/3	61018BP.79340DI	61018BP.7942DI	61018BP.7947DI

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*