

Compacte ronde inbouw LED spotlight met wit gelakte aluminium behuizing (RAL 9010). 30° kantelbaar. Zeer hoge kwaliteit NICHIA LED's met hoge kleurweergave (CRI>85) en anti verblindingslens (UGR<20). Geen lichtverlies boven het plafond. Standaard verkrijgbaar in warm wit (2700k). Uitermate geschikt als vervanging van halogeenspots in hallen, gangen, restaurants, en als aanlichting van objecten. Inclusief geïntegreerde constant current fase dimbare driver (tot maximaal 15% dimbaar). Direct aansluitbaar op 100-240V AC. Onderhoudsvrij en hoge levensduur verwachting 40.000 uur L90B10. Snelle montage. 3 jaar garantie (Ta -5°C ~ 35°C).

Compact round recessed LED spotlight with white painted aluminium housing (RAL 9010). 30° tiltable. Very high quality NICHIA LEDs with high colour rendering (CRI>85) and anti glare lens (UGR<20). Standard available in warm white (2700k). Very suitable as replacement for halogen spotlights in corridors, restaurants, bars and for lighting objects. Including integrated constant current trailing edge driver (dimnable to max. 15%) Direct connection to mains 100-240V AC. Low maintenance. Life expectancy 40.000 hours L90B10. Fast assembly. 3 years warranty (Ta -5°C ~ 35°C).

Watt Watts	Kleur Colour	Lumen* Lumen *	Graden Degrees	Diameter Ø (mm) Diameter Ø (mm)	Hoogte (mm) Height (mm)	Gatmaat Cutout	Gewicht (kg) Weight (kg)	Artikelnr. Article number
6w	2700k	550	36°	85	50	75	183	29648.6.27
10w	2700k	760	36°	85	60	75	210	29648.10.27

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



Opties:

- 3000K, 4000K en 5000K
- 60° lens
- Bewegingssensor(IR)



Aansluitnoeren (optioneel):


- Gemonteerde 2 meter snoer + stekker (2-pole)
29648.____-M2
- Gemonteerde 0,5 meter snoer + GST18i3® male
29648.____-GST

Options:

- 3000K, 4000K and 5000K
- 60° lens
- Motion Sensor (IR)

Connecting lead (optional):

- Assembled 2 meter wire + plug (2-pole)
29648.____-M2
- Assembled 0,5 meter wire + GST18i3® male
29648.____-GST



29648.10.27

10w 2700K
760lm 36°