


De Rafter is een koppelbaar slank pendel armatuur met voorzieningen voor de Tube 130 accent spot. De behuizing is vervaardigd uit zwart (RAL 9005) gelakt plaatstaal (optioneel wit RAL 9003). De geïntegreerde LED spotlights hebben een uitschuifbare kop voor maximale flexibiliteit. 350° draaibaar en 90° kantelbaar. Gefacetteerde hoogglans 99,98% aluminium reflector met helder gehard glazen afscherming (UGR<17). In combinatie met de optionele honingraat diffuser (UGR<14) zeer geschikt als accent en basisverlichting in hotels, en restaurants. Directe aansluiting op netspanning. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <3 (3000K). Vijf jaar garantie.

The Rafter is a connectable slim suspended luminaire with compact Tube 130 accent spot lights. Housing is made of black (RAL 9005) painted sheet metal (optionally white RAL 9003). The integrated round tiltable LED spot lights have an extractable luminaire head for maximum flexibility. Rotates through 350° and pivots through 90°. Facetted glossy 99,98% aluminium reflector with clear tempered glass diffuser. Low glare (UGR<17). In combination with the optional honey comb diffuser (UGR<14). Very suitable in hotels, bars and restaurants. Maintenance free and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <3 (3000K). Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Graden Degree	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	1-10V 1-10V	Dali Dali
9w	2700k	925	>80	20°	1,6	1/3	20045B.0920.270	20045B.0920.271	20045B.0920.272
13w	2700k	1225	>80	20°	1,6	1/3	20045B.1320.270	20045B.1320.271	20045B.1320.272
19w	2700k	1730	>80	20°	1,6	1/3	20045B.1920.270	20045B.1920.271	20045B.1920.272
28w	2700k	2240	>80	20°	1,6	1/3	20045B.2820.270	20045B.2820.271	20045B.2820.272
9w	2700k	895	>80	40°	1,6	1/3	20045B.0940.270	20045B.0940.271	20045B.0940.272
13w	2700k	1225	>80	40°	1,6	1/3	20045B.1340.270	20045B.1340.271	20045B.1340.272
19w	2700k	1680	>80	40°	1,6	1/3	20045B.1940.270	20045B.1940.271	20045B.1940.272
28w	2700k	2170	>80	40°	1,6	1/3	20045B.2840.270	20045B.2840.271	20045B.2840.272
9w	3000k	975	>80	20°	1,6	1/3	20045B.0920.30	20045B.0920.31	20045B.0920.32
13w	3000k	1300	>80	20°	1,6	1/3	20045B.1320.30	20045B.1320.31	20045B.1320.32
19w	3000k	1800	>80	20°	1,6	1/3	20045B.1920.30	20045B.1920.31	20045B.1920.32
28w	3000k	2340	>80	20°	1,6	1/3	20045B.2820.30	20045B.2820.31	20045B.2820.32
9w	3000k	980	>80	40°	1,6	1/3	20045B.0940.30	20045B.0940.31	20045B.0940.32
13w	3000k	1365	>80	40°	1,6	1/3	20045B.1340.30	20045B.1340.31	20045B.1340.32
19w	3000k	1890	>80	40°	1,6	1/3	20045B.1940.30	20045B.1940.31	20045B.1940.32
28w	3000k	2520	>80	40°	1,6	1/3	20045B.2840.30	20045B.2840.31	20045B.28240.32
9w	4000k	1025	>80	20°	1,6	1/3	20045B.0920.40	20045B.0920.41	20045B.0920.42
13w	4000k	1365	>80	20°	1,6	1/3	20045B.1320.40	20045B.1320.41	20045B.1320.42
19w	4000k	1890	>80	20°	1,6	1/3	20045B.1920.40	20045B.1920.41	20045B.1920.42
28w	4000k	2460	>80	20°	1,6	1/3	20045B.2820.40	20045B.2820.41	20045B.2820.42
9w	4000k	1030	>80	40°	1,6	1/3	20045B.0940.40	20045B.0940.41	20045B.0940.42
13w	4000k	1430	>80	40°	1,6	1/3	20045B.1340.40	20045B.1340.41	20045B.1340.42
19w	4000k	1985	>80	40°	1,6	1/3	20045B.1940.40	20045B.1940.41	20045B.1940.42
28w	4000k	2645	>80	40°	1,6	1/3	20045B.2840.40	20045B.2840.41	20045B.28240.42

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Opties:

- 1,5 meter snoer met 2-polige Schuko
- 0,5 meter snoer + GST18i3® connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3® and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5® Blue connector male (dim)
- 2700K, 3500k, 5000k of hogere CRI waarde 90/97
- Vlees, brood of Crisp White
- Speciale maten op aanvraag (lengte en breedte)
- Staalkabel set 2x4m (20045.PNDL.SET)
- Deksel en schroefjes (20045B.DEKSEL)

Options:

- 1,5m cable with Schuko 2-pin plug
- 0,5 meter cable + GST18i3® connector (non - dimmable)
- 0,5 meter cable + GST18i3® and BST14i2 connector (dim)
- 0,5 meter cable + GST18i5® Blue connector male (dim)
- 2700k, 3500k, 5000k or higher CRI values 90/97
- Meat, bread or Crisp White
- Special sizes on request (length and width)
- Suspension cables 2x4m (20045.PNDL.SET)
- Lid and screws (20045B.DEKSEL)




20045B.0920.270


9w 2700k 20° 925lm
ηLB 70%

Rafter


1L




1M



2



Zijaanzicht
Side view



PENDEL ARMATUREN *SUSPENDED LUMINAIRES*

Aantal spots No. of spots	Doervoergat Through hole	Type Type	Artikel nr. Article no.
1	1	1L	20045B.1L-BEGIN
1	1	1M	20045B.1M-BEGIN
2	1	2	20045B.2-BEGIN
1	2	1L	20045B.1L-MID
1	2	1M	20045B.1M-MID
2	2	2	20045B.2-MID
1	0	1L	20045B.1L-SINGLE
1	0	1M	20045B.1M-SINGLE
2	0	2	20045B.2-SINGLE

