

Rush Louvre UP/DOWN SUSPENDED



PENDEL ARMATUREN SUSPENDED LUMINAIRES

Elegant grijs of wit gelakt aluminium pendel armatuur met directe/indirecte lichtbundel. Voorzien van hoogwaardige Louvre diffuser met lage verblindingsgraad. Hoog voltage en hoog rendement LED lines (>120lm/w). Geschikt voor o.a. scholen, kantoren, recepties en galeriën. Alle elektronische compenten in de behuizing. Wordt geleverd inclusief 2 staalkabels (1m) met trapezium ophanging. Optie: aansluitsnoer + beschermkapje. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.



Elegant grey or white painted aluminium suspended luminaire with direct/indirect beam angle. Equipped with high quality Louvre diffuser with low glare. High voltage LED lines (>120lm/w). Suitable in schools, offices and receptions. All electronic components inside the housing. Delivered including 2 steel cables with Y-shaped suspension (1m). Power cable including protective cover, optional. Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.



Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI (Ra) CRI (Ra)	Lengte (mm) Length (mm)	Breedte (mm) Width (mm)	Hoogte (mm) Height (mm)	Gewicht (kg) Weight (kg)	Artikel nr. Article no.	Dali
39w	3000k	4791	>80	1370	225	35	6	21030G.39.30	21030G.39.32
39w	3000k	4791	>80	1370	225	35	6	21030W.39.30	21030W.39.32
67w	3000k	7918	>80	1370	225	35	6	21030G.67.30	21030G.67.32
67w	3000k	7918	>80	1370	225	35	6	21030W.67.30	21030W.67.32
49w	3000k	5985	>80	1670	225	35	7,5	21030G.49.30	21030G.49.32
49w	3000k	5985	>80	1670	225	35	7,5	21030W.49.30	21030W.49.32
84w	3000k	9895	>80	1670	225	35	7,5	21030G.84.30	21030G.84.32
84w	3000k	9895	>80	1670	225	35	7,5	21030W.84.30	21030W.84.32
39w	4000k	5043	>80	1370	225	35	6	21030G.39.40	21030G.39.42
39w	4000k	5043	>80	1370	225	35	6	21030W.39.40	21030W.39.42
67w	4000k	8335	>80	1370	225	35	6	21030G.67.40	21030G.67.42
67w	4000k	8335	>80	1370	225	35	6	21030W.67.40	21030W.67.42
49w	4000k	6300	>80	1670	225	35	7,5	21030G.49.40	21030G.49.42
49w	4000k	6300	>80	1670	225	35	7,5	21030W.49.40	21030W.49.42
84w	4000k	10.415	>80	1670	225	35	7,5	21030G.84.40	21030G.84.42
84w	4000k	10.415	>80	1670	225	35	7,5	21030W.84.40	21030W.84.42

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




21030W.set (wit/white)

21030G.set (grijs/grey)



Koppelstuk/Connector



21030G.39.30

39w 3000k 4791lm

62% down 38% up η LB 100%

melis lighting