

Professionele hoge kwaliteit 24VDC soft strip met hoge lumen per watt verhouding (tot 109lm/w), voor inbouw in koven, kasten, armaturen, etc. Hoogrendement 2835 LED op flexibele strip. IP20 en IP65 soft strip is aan de achterzijde voorzien van 3M tape (standaard 5 meter rol). De strip is aan beide zijden voorzien van 10cm snoer. Voor maximale lumen output tweezijdig voeden. IP65 variant is voorzien van een siliconen huls. Onderhoudsarm en hoge levensduurverwachting 35.000 uur bij Ta 25°C. Mac Adam <3. Twee jaar garantie.

Professional high quality 24VDC soft strip with high lumen per watt ratio (up to 109lm/w) mainly used for cove lighting, indoor decoration, backlighting and edge lighting. High efficiency 2835 LED's on a flexible strip. The IP20 and IP65 soft strip come with 3M tape on the back (standard 5 meter reel). Includes 10cm wire on both ends of the strip. For maximum lumen output and lifetime it is advised to power the strip on both ends. The IP65 soft strip comes with a silicon sleeve. Lifetime expectancy 35.000 at Ta 25°C. Mac Adam <3. Two years warranty.

LED's p/m LED's p/m	Voltage(DC) Voltage(DC)	Watt p/m Watt p/m	Kleur Color	Lumen* (p/m) Lumen* (p/m)	CRI (RA) CRI (RA)	Lengte(m) Length(m)	Breedte(mm) Width(mm)	Min. lengte(mm) min. length(mm)	Gewicht (per rol/kg) Weight(per reel/kg)	Artikelnr. (IP20) Article number (IP20)	Artikelnr. (IP65) Article number (IP65)
120	24v	9,6	2700k	700	>90	5	8	6-led (50mm)	0,1	SN12024XW2090	
120	24v	9,6	3000k	750	>90	5	8	6-led (50mm)	0,1	SN12024WW2090	
120	24v	9,6	4000k	780	>90	5	8	6-led (50mm)	0,1	SN12024WW2090	
60	24v	12	3000k	1140	>80	5	10 (13)	6-led (100mm)	0,1	SN6024WW20	SN6024WW65
60	24v	12	4000k	1200	>80	5	10 (13)	6-led (100mm)	0,1	SN6024NW20	SN6024NW65
120	24v	23	3000k	2280	>80	5	12 (15)	12-led (100mm)	0,1	SN12024WW20	SN12024WW65
120	24v	23	4000k	2400	>80	5	12 (15)	12-led (100mm)	0,1	SN12024NW20	SN12024NW65
240	24v	19,2	2700k	1350	>90	5	10	6-led (25mm)	0,1	SN24024XW2090	
240	24v	19,2	3000k	1450	>90	5	10	6-led (25mm)	0,1	SN24024WW2090	
240	24v	19,2	4000k	1550	>90	5	10	6-led (25mm)	0,1	SN24024WW2090	

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%

* wattage/lumen per meter wordt lager naarmate de LED strip langer wordt

* wattage/lumen per meter decreases with the increase of the strip length

Optioneel:

- 2700k of 6000k
- Rood, Geel, Amber, Groen of Blauw

Optional:

- 2700k or 6000k
- Red, Yellow, Amber, Green or Blue

