

Balvast opbouw LED armatuur voor gymzalen en sporthallen. Vervaardigd uit 2 mm wit gelakte (RAL 9003) plaatstalen behuizing. Het optische systeem bestaat uit een reeks mechanisch resistente pc-lenzen. Lage verblinding (UGR<21). Door brede uitstralingshoek .60° / >90° hoge gelijkmatigheid op werkvlak. Voorzien van hoog voltage LED met opalen afscherming. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B20, 100.000 uur L80B50). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Ball proof surface mounted LED luminaire for sport facilities and gyms. Extra strong white painted (RAL 9003) sheet metal (2mm) housing. The optical system consists of an array of mechanically resistant PC lenses. Steel reflector blades and cross wires. Low glare (UGR<21). With wide beam angle >60° / >90° for high uniformity on working area. High voltage LEDs behind opal diffuser. Standard available in CRI>80. Low maintenance and high life expectancy (50.000 hours L90B20, 100.000 uur L80B50). Colour stability, Mac Adam <3. Warranty 5 years.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI (Ra) CRI (Ra)	B (mm) W (mm)	L (mm) L (mm)	H (mm) H (mm)	kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dali Dali	EasySense EasySense
44w	3000k	6165	>80	300	400	75	1.9	1/3	61583WA.443060	61583WA.443260	61583WA.443760
78w	3000k	10.060	>80	300	400	75	1.9	1/3	61583WA.783060	61583WA.783260	61583WA.783760
67w	3000k	9320	>80	145	980	75	2.1	1/3	61583WB.673060	61583WB.673260	61583WB.673760
110w	3000k	14.335	>80	145	980	75	2.1	1/3	61583WB.1103060	61583WB.1103260	61583WB.1103760
134w	3000k	18.650	>80	300	980	75	4.1	1/3	61583WC.1343060	61583WC.1343260	61583WC.1343760
220w	3000k	28.670	>80	300	980	75	4.1	1/3	61583WC.2203060	61583WC.2203260	61583WC.2203760
92w	3000k	12.700	>80	145	1300	75	2.8	1/3	61583WD.923060	61583WD.923260	61583WD.923760
148w	3000k	19.135	>80	145	1300	75	2.8	1/3	61583WD.1483060	61583WD.1483260	61583WD.1483760
184w	3000k	15.910	>80	300	1300	75	5.6	1/3	61583WE.1843060	61583WE.1843260	61583WE.1843760
296w	3000k	38.265	>80	300	1300	75	5.6	1/3	61583WE.2963060	61583WE.2963260	61583WE.2963760

44w	4000k	6490	>80	300	400	75	1.9	1/3	61583WA.444060	61583WA.444260	61583WA.444760
78w	4000k	10.590	>80	300	400	75	1.9	1/3	61583WA.784060	61583WA.784260	61583WA.784760
67w	4000k	9810	>80	145	980	75	2.1	1/3	61583WB.674060	61583WB.674260	61583WB.674760
110w	4000k	15.090	>80	145	980	75	2.1	1/3	61583WB.1104060	61583WB.1104260	61583WB.1104760
134w	4000k	19.630	>80	300	980	75	4.1	1/3	61583WC.1344060	61583WC.1344260	61583WC.1344760
220w	4000k	30.180	>80	300	980	75	4.1	1/3	61583WC.2204060	61583WC.2204260	61583WC.2204760
92w	4000k	13.370	>80	145	1300	75	2.8	1/3	61583WD.924060	61583WD.924260	61583WD.924760
148w	4000k	20.140	>80	145	1300	75	2.8	1/3	61583WD.1484060	61583WD.1484260	61583WD.1484760
184w	4000k	26.750	>80	300	1300	75	5.6	1/3	61583WE.1844060	61583WE.1844260	61583WE.1844760
296w	4000k	40.280	>80	300	1300	75	5.6	1/3	61583WE.2964060	61583WE.2964260	61583WE.2964760

44w	3000k	6315	>80	300	400	75	1.9	1/3	61584WA.443090	61584WA.443290	61584WA.443790
78w	3000k	9890	>80	300	400	75	1.9	1/3	61584WA.783090	61584WA.783290	61584WA.783790
67w	3000k	9545	>80	145	980	75	2.1	1/3	61584WB.673090	61584WB.673290	61584WB.673790
110w	3000k	14.200	>80	145	980	75	2.1	1/3	61584WB.1103090	61584WB.1103290	61584WB.1103790
134w	3000k	19.105	>80	300	980	75	4.1	1/3	61584WC.1343090	61584WC.1343290	61584WC.1343790
220w	3000k	28.395	>80	300	980	75	4.1	1/3	61584WC.2203090	61584WC.2203290	61584WC.2203790
92w	3000k	12.975	>80	145	1300	75	2.8	1/3	61584WD.923090	61584WD.923290	61584WD.923790
148w	3000k	18.895	>80	145	1300	75	2.8	1/3	61584WD.1483090	61584WD.1483290	61584WD.1483790
184w	3000k	25.955	>80	300	1300	75	5.6	1/3	61584WE.1843090	61584WE.1843290	61584WE.1843790
296w	3000k	37.790	>80	300	1300	75	5.6	1/3	61584WE.2963090	61584WE.2963290	61584WE.2963790

44w	4000k	6650	>80	300	400	75	1.9	1/3	61584WA.444090	61584WA.444290	61584WA.444790
78w	4000k	10.410	>80	300	400	75	1.9	1/3	61584WA.784090	61584WA.784290	61584WA.784790
67w	4000k	10.050	>80	145	980	75	2.1	1/3	61584WB.674090	61584WB.674290	61584WB.674790
110w	4000k	14.950	>80	145	980	75	2.1	1/3	61584WB.1104090	61584WB.1104290	61584WB.1104790
134w	4000k	20.110	>80	300	980	75	4.1	1/3	61584WC.1344090	61584WC.1344290	61584WC.1344790
220w	4000k	29.890	>80	300	980	75	4.1	1/3	61584WC.2204090	61584WC.2204290	61584WC.2204790
92w	4000k	13.660	>80	145	1300	75	2.8	1/3	61584WD.924090	61584WD.924290	61584WD.924790
148w	4000k	19.890	>80	145	1300	75	2.8	1/3	61584WD.1484090	61584WD.1484290	61584WD.1484790
184w	4000k	27.320	>80	300	1300	75	5.6	1/3	61584WE.1844090	61584WE.1844290	61584WE.1844790
296w	4000k	39.780	>80	300	1300	75	5.6	1/3	61584WE.2964090	61584WE.2964290	61584WE.2964790

* Lichtstroom van armatuur, tolerantie van +/- 10%



* Luminaire luminous flux, tolerance of +/- 10%

**Opties:**

- Daglicht en bewegingsregeling ingebouwd in de diffuser
- EasySense Sensor
- CRI >90

Options:

- Daylight and motion control sensor build into the diffuser
- EasySense Sensor
- CRI >90

**61583WA.443060**
 44W 3000k 6165lm
 ηLB 100%
**61584WA.443090**
 44W 3000k 6315lm
 ηLB 100%

