


Balvast opbouw LED armatuur voor gymzalen en sporthallen. Vervaardigd uit 0,5mm wit gelakte (RAL 9003) plaatstalen behuizing met decoratieve afgeronde hoeken. Voorzien van plaatstaal reflector met stalen dwarsbladen en stangen. Lage verblinding (UGR<21). Door brede uitstralingshoek >85° hoge gelijkmatigheid op werkvlak. Voorzien van hoog voltage LED met opalen afscherming. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B20, 100.000 uur L80B50). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Ball proof surface mounted LED luminaire for sport facilities and gyms. Extra strong white painted (RAL 9003) sheet metal (0,5mm) housing with bevelled edges. Steel reflector blades and cross wires. Low glare (UGR<21). With wide beam angle >85° for high uniformity on working area. High voltage LEDs behind opal diffuser. Standard available in CRI>80. Low maintenance and high life expectancy (50.000 hours L90B20, 100.000 uur L80B50). Colour stability, Mac Adam <3. Warranty 5 years.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI (Ra) CRI (Ra)	B (mm) W (mm)	L (mm) L (mm)	H (mm) H (mm)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dali Dali	EasySense EasySense
47w	3000k	5939	>80	355	1255	85	6	1/3	29611W.A47.30	29611W.A47.32	29611W.A47.37
95w	3000k	11.461	>80	355	1255	85	6	1/3	29611W.A95.30	29611W.A95.32	29611W.A95.37
70w	3000k	9179	>80	355	1555	85	7,5	1/3	29611W.B70.30	29611W.B70.32	29611W.B70.37
102w	3000k	12.821	>80	355	1555	85	7,5	1/3	29611W.B102.30	29611W.B102.32	29611W.B102.37
142w	3000k	17.087	>80	355	1555	85	7,5	1/3	29611W.B142.30	29611W.B142.32	29611W.B142.37
145w	3000k	15.875	>80	450	1555	85	14	1/3	29611W.C145.30	29611W.C145.32	29611W.C145.37
205w	3000k	22.369	>80	450	1555	85	14	1/3	29611W.C205.30	29611W.C205.32	29611W.C205.37
47w	4000k	6251	>80	355	1255	85	6	1/3	29611W.A47.40	29611W.A47.42	29611W.A47.47
95w	4000k	12.065	>80	355	1255	85	6	1/3	29611W.A95.40	29611W.A95.42	29611W.A95.47
70w	4000k	9662	>80	355	1555	85	7,5	1/3	29611W.B70.40	29611W.B70.42	29611W.B70.47
102w	4000k	13.496	>80	355	1555	85	7,5	1/3	29611W.B102.40	29611W.B102.42	29611W.B102.47
142w	4000k	17.986	>80	355	1555	85	7,5	1/3	29611W.B142.40	29611W.B142.42	29611W.B142.47
145w	4000k	16.710	>80	450	1555	85	14	1/3	29611W.C145.40	29611W.C145.42	29611W.C145.47
205w	4000k	23.546	>80	450	1555	85	14	1/3	29611W.C205.40	29611W.C205.42	29611W.C205.47

\* Lichtstroom van armatuur, tolerantie van +/- 10%

\* Luminaire luminous flux, tolerance of +/- 10%



## OPBOUW ARMATUREN SURFACE MOUNTED LUMINAIRES




### Opties:

- Daglicht en bewegingsregeling ingebouwd in de diffuser
- EasySense Sensor
- CRI >90

### Options:

- Daylight and motion control sensor build into the diffuser
- EasySense Sensor
- CRI >90



**29611W.A47.30**  
47W 3000k 5939lm  
ηLB 100%