



Decoratief inlegarmatuur met standaard afmetingen voor systeemplafonds (M600) of gipsplafonds met hoog armatuur rendement (>125lm/w). Vervaardigd uit witgelakt (RAL 9003) plaatstaal. Centrale verlichting verlichting via micro prisma afscherming. Hierdoor zeer goed toepasbaar in gangen, kantoren, klaslokalen, en andere werkkruimtes waar hoge eisen aan comfort worden gesteld. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Decorative recessed luminaire with standard measurements for suspended ceilings (M600) or plasterboard ceilings with high luminaire efficiency (>125lm/w). Housing made of white painted (RAL 9003) sheet metal. Central lighting through micro prisma diffusor. Very suitable in corridors, offices, classrooms and other working areas where there are high demands for comfortable light. Low maintenance and high life expectancy (50.000 hours L90B10). Colour stability, Mac Adam <3. Warranty 5 years.

Wattage Watts	Kleur Colour	Lumen Lumen	CRI (Ra) CRI (Ra)	Breedte (mm) Width (mm)	Lengte (mm) Length (mm)	Hoogte (mm) Height (mm)	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dali Dali	EasySense EasySense
26w	3000k	3135	>80	595	595	75	3,25	1/3	29511MA.26.30	29511MA.26.32	29511MA.26.37
33w	3000k	3895	>80	595	595	75	3,25	1/3	29511MA.33.30	29511MA.33.32	29511MA.33.37
38w	3000k	4465	>80	595	595	75	3,25	1/3	29511MA.38.30	29511MA.38.32	29511MA.38.37
26w	3000k	3135	>80	295	1195	75	3,25	1/3	29511MB.26.30	29511MB.26.32	29511MB.26.37
33w	3000k	3895	>80	295	1195	75	3,25	1/3	29511MB.33.30	29511MB.33.32	29511MB.33.37
38w	3000k	4465	>80	295	1195	75	3,25	1/3	29511MB.38.30	29511MB.38.32	29511MB.38.37
26w	4000k	3300	>80	595	595	75	3,25	1/3	29511MA.26.40	29511MA.26.42	29511MA.26.47
33w	4000k	4100	>80	595	595	75	3,25	1/3	29511MA.33.40	29511MA.33.42	29511MA.33.47
38w	4000k	4700	>80	595	595	75	3,25	1/3	29511MA.38.40	29511MA.38.42	29511MA.38.47
26w	4000k	3300	>80	295	1195	75	3,25	1/3	29511MB.26.40	29511MB.26.42	29511MB.26.47
33w	4000k	4100	>80	295	1195	75	3,25	1/3	29511MB.33.40	29511MB.33.42	29511MB.33.47
38w	4000k	4700	>80	295	1195	75	3,25	1/3	29511MB.38.40	29511MB.38.42	29511MB.38.47

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Opties:

- Daglichtregeling
- Bewegingsmelder
- Daglichtregeling & bewegingssensor
- GST18i3® connector + BST14i2 connector
- GST18i5® connector
- Andere RAL kleur

Optional:

- Daylight control sensor
- Motion sensor
- Daylight control & motion sensor
- GST18i3® connector + BST14i2 connector
- GST18i5® connector
- Different RAL colour



29511MA.26.30

26w 3000k 3135lm
ηLB 100%