


Rond LED armatuur voor wand of plafondmontage. Zeer diffuus en krachtig licht met goede kleurweergave ($R_a > 80$). Zeer slagvaste en weerbestendige polycarbonaat (wit, zwart of grijs) behuizing met opalen difuser. Alle elektronische componenten in de behuizing. Aansluiting op voeding via kroonsteen in de behuizing. Invoer voeding via achterzijde van het armatuur met mogelijkheid tot doorlussen. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam < 3 . Vijf jaar garantie.

Round LED luminaire for wall or ceiling. Diffuse light distribution with good colour rendering ($R_a > 80$). Highly protected against external impacts and waterproof. Housing made of polycarbonate (white, black or grey) with opal diffuser. All electronic components inside the luminaire. Connection through the back of the luminaire directly to connector block. Suitable for series connection. Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam < 3 . Fast and easy mounting with springs. Five years warranty.

Wattage Watts	Ring kleur Ring Colour	Kleur Color	Lumen* Lumen*	kg	Diameter (mm) Diameter (mm)	Hoogte (H) Height (h)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Bewegingssensor Motionsensor
14w	wit/white	3000k	1300	1,65	335	110	1/3	29638W.14.30	29638W.14.30S
14w	wit/white	4000k	1400	1,65	335	110	1/3	29638W.14.40	29638W.14.40S
14w	grijs/grey	3000k	1300	1,65	335	110	1/3	29638G.14.30	29638G.14.30S
14w	grijs/grey	4000k	1400	1,65	335	110	1/3	29638G.14.40	29638G.14.40S
14w	zwart/black	3000k	1300	1,65	335	110	1/3	29638B.14.30	29638B.14.30S
14w	zwart/black	4000k	1400	1,65	335	110	1/3	29638B.14.40	29638B.14.40S
18w	wit/white	3000k	1650	1,65	335	110	1/3	29638W.18.30	29638W.18.30S
18w	wit/white	4000k	1750	1,65	335	110	1/3	29638W.18.40	29638W.18.40S
18w	grijs/grey	3000k	1650	1,65	335	110	1/3	29638G.18.30	29638G.18.30S
18w	grijs/grey	4000k	1750	1,65	335	110	1/3	29638G.18.40	29638G.18.40S
18w	zwart/black	3000k	1650	1,65	335	110	1/3	29638B.18.30	29638B.18.30S
18w	zwart/black	4000k	1750	1,65	335	110	1/3	29638B.18.40	29638B.18.40S

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Opties:

- Geïntegreerde bewegingssensor
- Corridor functie

Options:

- Integrated motionsensor
- Corridor function



29638W.14.30
14w 3000k 1330lm
 η_{LB} 51%